



ermesceramichespa

sede legale: via giardini nord, 22 • 41043 formigine (mo)
magazzino e uffici: via statale 467, 171 • 42013 veggia (re) • italy
tel. +39 0536 824242 • 991511
fax +39 0536 824777 (comm.) • 991599 (amm.)
e-mail: info@ermes-ceramiche.it
www.ermes-ceramiche.it • www.aurelia-ceramiche.it
cap. soc. € 743600,00 i.v. • rea mo 263545 • reg. imprese mo 35783

DECLARATION OF PERFORMANCE

No. 002CPR305/2011

1. Dry-pressed ceramic tiles, with water absorption $E_b > 10\%$
2. Intended use: internal walls
3. ERMES CERAMICHE SPA
Strada Statale 467, n. 171 – 42013 Veggia (RE) – ITALY
4. System of assessment and verification of constancy of performance (AVCP): 4
5. Not applicable
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14111:2012
Release of dangerous substance, for: <ul style="list-style-type: none">• Cadmium• Lead	NPD NPD	
Breaking strenght	$\frac{\nabla}{\Delta}$ < 7,5 mm: > 700 N ≥ 7,5 mm: > 1300 N	
Tactility	NPD	
Bond strength/adhesion, for: type C1	≥ 0,5 N/mm ²	
Durability, for: <ul style="list-style-type: none">• internal use	Resistant	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by

Veggia(RE), June 26th, 2013

Ing. Liparulo Paolo
Amministratore Delegato

ermes
aurelia



ermesceramichespa

sede legale: via giardini nord, 22 • 41043 formigine (mo)
magazzino e uffici: via statale 467, 171 • 42013 veggia (re) • italy
tel. +39 0536 824242 • 991511
fax +39 0536 824777 (comm.) • 991599 (amm.)
e-mail: info@ermes-ceramiche.it
www.ermes-ceramiche.it • www.aurelia-ceramiche.it
cap. soc. € 743600,00 iv. • rea mo 263545 • reg. imprese mo 35783



Ermes Ceramiche Spa

Strada Statale 467, nr. 171 42013 Veggia (RE) Italy

05
002CPR305/2011

EN 14411:2012

Piastrelle di ceramica pressate a secco ,con assorbimento d'acqua E_b>10%, per rivestimento interno

Dry-pressed ceramic tiles, with water absorption E_b>10%, for internal walls

Carreaux et dalles céramiques pressées à sec ,à absorption d'eau E_b>10%, pour revêtements de murs intérieurs

Trockengepresste keramische Fliesen und Platten mit einer Wasseraufnahme E_b>10%, wandfliesen fuer innenbereich

Reazione al fuoco Reaction to fire /Réaction au feu/ Feuerreaktion	A1
Resistenza alla rottura Breaking strenght/Résistance à la rupture/ Bruchlast	$\frac{\nabla}{\Delta}$ < 7,5 mm: > 700 N $\frac{\nabla}{\Delta}$ ≥ 7,5 mm: > 1300 N
Resistenza all'adesione Bond strenght/ Résistance à l'adhésion/ Haftzugfestigkeit - tipo/ type C1	≥ 0,5 N/mm ²
Durabilità / Durability/Durabilité/Haltbarkeit • uso interno/ internal use/ utilisation en intérieur / internen gebrauch	resistente/resistant/ résistant/beständig