

## Product- and Environmental Declaration Collection: Lexington

Art No: 1850 - 1884

Collection: Lexington

Type: Wallcovering non-woven class 1 Weight: 75-190 g/m<sup>2</sup>

### Environmental mark

Fulfills the IGI:s trade standards

(IGI = International Wall covering Manufacturers' Association)

### Product contents

All wallcoverings from WallVision are free from PVC, heavy metals and other environmental harmful substances. All inks are waterbased.

The wallcoverings Components	Total weight percent	Weight-percent	Specifications of the components composition	Contains substances from the:		
				Limit-list*	PRIO-list*	Allergy and ...*
Non-Woven	65-100%	40-85%	Cellulose (TCF)	---	---	---
		15-30%	Synthetic fibres+film	---	---	---
		0-30%	Vac/Acrylic polymer	---	---	---
		15-25%	Filler	---	---	---
Ink	0-35%	65-100%	Pigment Filler	---	---	---
		0-30%	Vac/Acrylic polymer	---	---	---

\*Swedish State Chemical Inspection's Limitlist, PRIO-list

Formaldehyde in combined form exists naturally in wood being used in production of paper. Analysis of wallcoverings therefore shows tracks of formaldehyde. The quantities though are essential lower than the valid limit.

### Usage

The wallcovering can be used in all areas except wet areas such as bathrooms etc. Suitable adhesive is a machine adjusted adhesive.

### Emissions

Determination of the emission factor for VOC\* and identification of dominating substances has been made at the Swedish Testing- and Research Institute according to the FLEC-method\*\*. The test results is below the quantitative detection limit (< 10µg/m<sup>2</sup> x h)

\* VOC=Volatile Organic Compounds

\*\* FLEC=Field and Laboratory Emission Cell

### Colour fastness to light

Very good colour fastness to light 6-8. The highest value is 8.

# WallVision

## **Packaging**

The wallcovering rolls are wrapped into a thin recyclable polyethylene film before being packed into a corrugated cardboard carton.

In average 25 gr packaging is being used per kg wallcovering.

The average transport volume (incl. packaging) per kg wallcovering is about 4 dm<sup>3</sup>.

Return of packaging material to WallVision is not possible.

The packaging material is partly produced from recycled fibres.

## **Transport**

The wallcoverings are transported via trucks from our central warehouse in Borås, Sweden.

WallVision is connected to the Swedish REPA-register. Organisation number: 556423-2824.

## **Care instructions**

The wallcoverings have high washability. Stains are treated as follows:

- Wet the stain with a cloth or a sponge using soapy water or detergent.
- Use plenty of lukewarm water to get off all soap rests.
- Wipe off the over amount of water and leave the wallcovering to selfdry.
- Avoid to get water in the joints where the wallcovering is unprotected.

## **Estimated lifetime**

Estimated lifetime of the wallcovering is 10-15 years..

## **Recycling and waste**

The wallcovering can be recycled as energy at combustion.

All excess inks are being reused in production.

No wallcovering waste is considered as hazardous waste.

In order to achieve and maintain necessary wallcovering strength and fulfil WallVision's quality standards no recycled material is included in the wallcovering.

## **Production**

WallVision's emission of solvents is below existing limits for concession's permission according to the Swedish Environmental Protection Law.

## **Quality**

WallVision is certificated according to the international quality standard ISO 9001, certificate number 10 59.