

## **DECLARATION OF PERFORMANCE**

in compliance with the CPR n. 305/2011 Nr. 001 GP

- 1. Unique identification code if the product type:
- Dry pressed Ceramic Tiles with water absorption  $E_b \le 0.5\%$
- 2. Intended use(s): For internal and external walls and floorings
- 3. Name or registered trade mark and contact address of the manufacturer : ABK Group Industrie Ceramiche S.p.A., Via San Lorenzo n. 24/A 41034 Finale Emilia (MO) Italy.
- 4. System(s) of assessment and verification of constancy of performance (AVCP): Systems 4.
- 5. Name and identification number of notified laboratory, if relevant: Not applicable

- Task(s) carried outAVCP systemsDocument issued and date of issue

Declared performance

Essential characteristics	Performance	<b>Harmonised Tecnical Specification</b>
Reaction to fire	A1 <sub>fl</sub> + A1	Decision 96/603/CE as amended
Release of dangerous substance, for:		
- Cadmium	NPD	EN14411 : 2012
- Lead	NPD	
Breaking strength	> 1300 N	
Modulus of rupture	≥ 35 N/mm <sup>2</sup>	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
- Cementitious adhesive, type C2	> 1 N/mm <sup>2</sup>	
Thermal shock resistance	Pass	
Durability for:		
- Internal use	Pass	
- External use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Technical Manager Dott. Ing. Michelangelo	Fortuna
Name and function  Finale Emila, 28 June 2013  Place and date of issue	Signature